



BEST MOTORS
IMPORT SALES AND SERVICE
1235 UNIVERSITY AVE.
ROCHESTER 7, NEW YORK

Presenting the 1962 model with many new features

VOLVO 122

Specifications



* Engine 90 b.h.p. SAE

Four-cylinder in-line with overhead valves and crankshaft carried in five bearings.

Bore	3.313"
Stroke	3.15"
Capacity	1.78 liters
Compression ratio	8.5:1
Max. output	90 b.h.p. (SAE) at 5,000 r.p.m.
Max. torque	101 lb.ft. (SAE) at 3,500 r.p.m.
Carburetors	Two EU horizontal carburetors
Full flow oil filter	

* Cooling system

Effective radiator. Thermostat-controlled water circulation with by-pass valve.

* Battery

Voltage	12 V
Capacity	60 amp. hours

* Generator

Fan-cooled with automatic voltage control.
Capacity Max. 10 A.

* Starter motor

Output 1 h.p.
The starter is built into the ignition switch which also has an extra position where all the electrical equipment can be used while the engine is not running.

The ignition switch and the ignition coil are connected by means of a tamper-proof armored cable.

* Clutch

Hydraulically-operated 8 $\frac{1}{2}$ " single dry plate clutch.

Transmission

Fully synchronized and quiet running.
Ratios: 1st speed 3.13:1
2nd speed 1.99:1
3rd speed 1.36:1
4th speed 1:1
Reverse 3.25:1

Propeller shaft

Divided for vibration-free operation. The center bearing is mounted in sound and vibration-dampening rubber blocks. The center bearing ball bearing requires no servicing.

Rear axle

Hypoid type
Ratio 4.1:1

Steering gear

Cam and roller type
Steering box ratio 15.5:1
Left lock — right lock 3 $\frac{1}{4}$ turns of steering wheel
Turning circle Approx. 32 ft.

Suspension, front

Independent suspension with coil springs and control arms are carried in rubber bushings and ball joints.
Stabilizer.

Suspension, rear

Fixed longitudinal support arms and torque rods.
Track bar.
Coil springs.

Shock absorbers

Double-acting, hydraulic telescopic shock absorber front and rear.

* Footbrakes

Front:
Hydraulic disk brake of the three-cylinder type. Splash-protected and self-adjusting.
Disks 10 $\frac{1}{2}$ " x $\frac{1}{4}$ "
Brake friction area on each front wheel 44 $\frac{1}{2}$ sq.in.
Rear:
V-type drum brakes. Hydraulic and self-centering.
Brake friction area on each rear wheel 32 $\frac{1}{2}$ sq.in.

Handbrake

Operates separately on rear wheels.
Handbrake lever located beside driving seat.

Wheels and tires

Pressed disk wheels. All wheels balanced. Tubeless 5.90 — 15" tires.

Body

Integral construction, all-welded steel body, fully rust-proofed by modern methods.

Fuel tank

Located at rear.
Capacity 12 US gal.

Lighting equipment

Flasher, direction indicators front and rear with optical and acoustic warning signals.
Combined stop and tail lights.
The inner lighting goes on when either of the front doors is opened.
Instrument lighting is rheostat-controlled.
Map-reading lamp.

Instrumentation

Combined instrument with speedometer, fuel gauge and water temperature gauge.
Mileometer and trip meter.
Warning lamps for charging, oil pressure, full headlights, direction indicators.

Other equipment

Horn ring on steering wheel.
Foot dimmer switch.
Direction indicator lever with automatic return.
Heater and ventilation equipment.
Thermostat-controlled heater. Low-speed fan with two speeds.
Electric windshield wipers with two speeds and automatic return.
Nozzles for windshield washer.
Double padded sun visors.
Dazzle-free rear view mirror.
Space available for fitting of radio and loudspeaker.
Pockets on front doors.
Cigarette lighter.
Ashtrays front and rear.
Tool kit and jack.
Spare wheel.

Safety belt attachments

Safety belt attachments for front and rear seat belts.

Main dimensions and weight

Wheelbase	102 $\frac{1}{2}$ "
Track, front	51 $\frac{1}{2}$ "
Track, rear	51 $\frac{1}{4}$ "
Overall length	175"
Overall width	63 $\frac{1}{4}$ "
Overall height, unloaded	59 $\frac{1}{4}$ "
Curb weight	2405 lb.

The factory reserves the right to modify prices, design and equipment.



AB VOLVO
GÖTEBORG SWEDEN

importers:
VOLVO IMPORT, INC.
402 Hudson Terrace, Englewood Cliffs, New Jersey
distributors:
VOLVO DISTRIBUTING, INC.
402 Hudson Terrace, Englewood Cliffs, New Jersey
SWEDISH MOTOR IMPORT, INC.
3100 West 12th Street, Houston 26, Texas

VOLVO WESTERN DISTRIBUTING, INC.
11915 Avenida De las, Sherman Oaks, Calif.

In Canada:
VOLVO (CANADA) LTD.
Head Office: 440 Constock Road, Scarborough (Toronto), Ont.
Branch Office: 1110 W. Georgia St., Vancouver 5, B. C.

DEALERS: